



## Kellems® Wire Management Products

### Standard Duty Support Grips

Single Eye, Single Weave, Tin-Coated Bronze

#### WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-42 through T-46.



Single Eye, Closed Mesh



Single Eye, Split Mesh, Lace Closing



Single Eye, Split Mesh, Rod Closing

#### Single Eye, Closed Mesh\*

For permanent support when cable end is available to be installed through grip.

| Cable Diameter Range Inches (cm) | Approx. Breaking Strength Lbs. (N) | E Inches (cm) | M Inches (cm) | Catalog Number |
|----------------------------------|------------------------------------|---------------|---------------|----------------|
| .50"-.62" (1.27-1.57)            | 530 (2,357)                        | 7" (17.78)    | 10" (25.40)   | 02201013       |
| .63"-.74" (1.60-1.88)            | 790 (3,514)                        | 8" (20.32)    | 10" (25.40)   | 02201014       |
| .75"-.99" (1.90-2.51)            | 1,020 (4,537)                      | 8" (20.32)    | 13" (33.02)   | 02201015       |
| 1.00"-1.24" (2.54-3.15)          | 1,610 (7,161)                      | 9" (22.86)    | 14" (35.56)   | 02201017       |
| 1.25"-1.49" (3.17-3.78)          | 1,610 (7,161)                      | 10" (25.40)   | 15" (38.10)   | 02201018       |
| 1.50"-1.74" (3.81-4.42)          | 1,610 (7,161)                      | 12" (30.48)   | 17" (43.18)   | 02201019       |
| 1.75"-1.99" (4.44-5.05)          | 2,150 (9,563)                      | 14" (35.56)   | 19" (48.26)   | 02201020       |
| 2.00"-2.49" (5.08-6.32)          | 3,260 (14,500)                     | 16" (40.64)   | 21" (53.34)   | 02201021       |
| 2.50"-2.99" (6.35-7.59)          | 3,260 (14,500)                     | 18" (45.72)   | 23" (58.42)   | 02201022       |
| 3.00"-3.49" (7.62-8.86)          | 4,900 (21,795)                     | 21" (53.34)   | 25" (63.50)   | 02201023       |
| 3.50"-3.99" (8.89-10.13)         | 4,900 (21,795)                     | 24" (60.96)   | 27" (68.58)   | 02201024       |

#### Single Eye, Split Mesh, Lace Closing\*

For permanent support when cable end is not available.

| Cable Diameter Range Inches (cm) | Approx. Breaking Strength Lbs. (N) | E Inches (cm) | M Inches (cm) | Catalog Number |
|----------------------------------|------------------------------------|---------------|---------------|----------------|
| .50"-.62" (1.27-1.57)            | 530 (2,357)                        | 7" (17.78)    | 10" (25.40)   | 02202013       |
| .63"-.74" (1.60-1.88)            | 790 (3,514)                        | 8" (20.32)    | 10" (25.40)   | 02202014       |
| .75"-.99" (1.90-2.51)            | 1,020 (4,537)                      | 8" (20.32)    | 13" (33.02)   | 02202015       |
| 1.00"-1.24" (2.54-3.15)          | 1,610 (7,161)                      | 9" (22.86)    | 14" (35.56)   | 02202017       |
| 1.25"-1.49" (3.17-3.78)          | 1,610 (7,161)                      | 10" (25.40)   | 15" (38.10)   | 02202018       |
| 1.50"-1.74" (3.81-4.42)          | 1,610 (7,161)                      | 12" (30.48)   | 17" (43.18)   | 02202019       |
| 1.75"-1.99" (4.44-5.05)          | 2,150 (9,563)                      | 14" (35.56)   | 19" (48.26)   | 02202020       |
| 2.00"-2.49" (5.08-6.32)          | 3,260 (14,500)                     | 16" (40.64)   | 21" (53.34)   | 02202021       |
| 2.50"-2.99" (6.35-7.59)          | 3,260 (14,500)                     | 18" (45.72)   | 23" (58.42)   | 02202022       |
| 3.00"-3.49" (7.62-8.86)          | 4,900 (21,795)                     | 21" (53.34)   | 25" (63.50)   | 02202023       |
| 3.50"-3.99" (8.89-10.13)         | 4,900 (21,795)                     | 24" (60.96)   | 27" (68.58)   | 02202024       |

#### Single Eye, Split Mesh, Rod Closing\*

For support when cable end is not available.

| Cable Diameter Range Inches (cm) | Approx. Breaking Strength Lbs. (N) | E Inches (cm) | M Inches (cm) | Catalog Number |
|----------------------------------|------------------------------------|---------------|---------------|----------------|
| .50"-.62" (1.27-1.57)            | 790 (3,514)                        | 7" (17.78)    | 8.5" (21.59)  | 02203013       |
| .63"-.74" (1.60-1.88)            | 790 (3,514)                        | 8" (20.32)    | 8.5" (21.59)  | 02203014       |
| .75"-.99" (1.90-2.51)            | 1,020 (4,537)                      | 8" (20.32)    | 10.5" (26.67) | 02203015       |
| 1.00"-1.24" (2.54-3.15)          | 1,610 (7,161)                      | 9" (22.86)    | 12.5" (31.75) | 02203017       |
| 1.25"-1.49" (3.17-3.78)          | 1,610 (7,161)                      | 10" (25.40)   | 14.5" (36.83) | 02203018       |
| 1.50"-1.74" (3.81-4.42)          | 1,610 (7,161)                      | 12" (30.48)   | 15.5" (39.37) | 02203019       |
| 1.75"-1.99" (4.44-5.05)          | 2,150 (9,563)                      | 14" (35.56)   | 16.5" (41.91) | 02203020       |
| 2.00"-2.49" (5.08-6.32)          | 3,260 (14,500)                     | 16" (40.64)   | 19.5" (49.53) | 02203021       |
| 2.50"-2.99" (6.35-7.59)          | 3,260 (14,500)                     | 18" (45.72)   | 21.5" (54.61) | 02203022       |
| 3.00"-3.49" (7.62-8.86)          | 5,750 (25,576)                     | 21" (53.34)   | 23.5" (59.69) | 02203023       |
| 3.50"-3.99" (8.89-10.13)         | 5,750 (25,576)                     | 24" (60.96)   | 25.5" (64.77) | 02203024       |

Note: E-Eye length.

M-Mesh length at nominal diameter.

\* Change catalog number from 022 to 024 for stainless steel. Consult factory for availability.