



WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-71 through T-76.

Non-Insulated, Wide Range Strain Relief

Thread Size	Cable Diameter Range Inches (cm)	Mesh Length @ Nom. Dia. Inches (cm)	Catalog Number
½ N.P.T.	.24"-.32" (.61-.81)	3.25" (8.25)	073031200
½ N.P.T.	.32"-.43" (.81-1.09)	3.75" (9.52)	073031201
½ N.P.T.	.43"-.54" (1.09-1.37)	4.75" (12.06)	073031202
¾ N.P.T.	.54"-.73" (1.37-1.85)	6.5" (16.51)	073031203
1 N.P.T.	.73"-.97" (1.85-2.46)	7" (17.78)	073031204
1¼ N.P.T.	.97"-1.25" (2.46-3.17)	9" (22.86)	073031205
PG29*	.73"-.97" (1.85-2.46)	7" (17.78)	073PG291204

Note: * Panzergewinde.



Non-Insulated

Insulated, Wide Range Strain Relief with Insulating Bushing

Thread Size	Cable Diameter Range Inches (cm)	Mesh Length @ Nom. Dia. Inches (cm)	Dim. A In. (cm)	Min. Space Between Grips In. (cm)	Catalog Number
½ N.P.S.	.24"-.32" (.61-.81)	3.25" (8.25)	1" (2.54)	1.25" (3.17)	073031206
½ N.P.S.	.32"-.43" (.81-1.09)	3.75" (9.52)	1" (2.54)	1.25" (3.17)	073031207
½ N.P.S.	.43"-.54" (1.09-1.37)	4.75" (12.06)	1" (2.54)	1.25" (3.17)	073031208
¾ N.P.S.	.54"-.73" (1.37-1.85)	6.5" (16.51)	1" (2.54)	1.5" (3.81)	073031209
1 N.P.S.	.73"-.97" (1.85-2.46)	7" (17.78)	1.313" (3.02)	1.75" (4.44)	073031210
1¼ N.P.S.	.97"-1.25" (2.46-3.17)	9" (22.86)	1.313" (3.02)	2.25" (5.71)	073031211
1½ N.P.T.	1.25"-1.50" (3.17-3.81)	11.75" (29.84)	1.313" (3.02)	2.5" (6.35)	073031212
2 N.P.T.	1.50"-1.70" (3.81-4.32)	13.25" (33.65)	1.375" (3.49)	3.25" (8.25)	073031213
2½ N.P.T.	1.70"-2.00" (4.32-5.08)	13.5" (34.29)	1.5" (3.81)	3.625" (9.21)	073031214
2½ N.P.T.	2.00"-2.45" (5.08-6.22)	13.75" (34.92)	1.5" (3.81)	3.625" (9.21)	073031215



Insulated