Rittal - The System.

Faster – better – everywhere.

Enclosure Heaters with fan – SK 3105.420

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Enclosure Heaters with fan - SK 3105.420

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Supply includes: PTC heater with fan

Quick-connection terminal

Fasteners

Note: For precise temperature control inside the enclosure, we recommend using the enclosure

internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, hygrostat is recommended to regulate heating.

In larger enclosures, even heat distribution is best achieved by installing several low-output

heaters.

The installation of heaters is generally advisable, in order to prevent condensation.

Product features

Continuous thermal output at 10°C:

355 W - 400 W

Note: Continuous thermal output with fan

Rated operating voltage:

115 V, 1~, 50 Hz/60 Hz

Dimensions:

Height: 200 mm (7.9 ") Width: 103 mm (4.1 ")

Depth: 103 mm (4.1 ")

Miniature circuitbreaker/fuse: 6 A

Integrated fan:

yes

Packaging unit:

1 pc(s).

Weight/packaging unit:

1.22 kg (2.7 lb.)

© Rittal 2018

1

EAN: 4028177662902 Customs tariff number: 85162999 ETIM 6.0: EC000737 ETIM 5.0: EC000737 eCl@ss 8.0/8.1: 27180710 eCl@ss 7.0/7.1: 27180710 eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals Approval overview CSA UR + C-UR VDE Certificates: EAC Declarations: Declaration of conformity		
number: ETIM 6.0: EC000737 ETIM 5.0: EC000737 eCl@ss 8.0/8.1: 27180710 eCl@ss 7.0/7.1: 27180710 eCl@ss 6.0/6.1: 27180710 Product description (long): Approvals Approval overview CSA UR + C-UR VDE Certificates: EAC	EAN:	4028177662902
ETIM 5.0: EC000737 eCl@ss 8.0/8.1: 27180710 eCl@ss 7.0/7.1: 27180710 eCl@ss 6.0/6.1: 27180710 eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC		85162999
eCl@ss 8.0/8.1: 27180710 eCl@ss 7.0/7.1: 27180710 eCl@ss 6.0/6.1: 27180710 eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC	ETIM 6.0:	EC000737
eCl@ss 7.0/7.1: 27180710 eCl@ss 6.0/6.1: 27180710 eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC	ETIM 5.0:	EC000737
eCl@ss 6.0/6.1: 27180710 eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals Approval overview CSA UR + C-UR VDE Certificates: EAC	eCl@ss 8.0/8.1:	27180710
eCl@ss 5.1/5.1.4: 27180710 Product description (long): SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm (long): Approvals Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC	eCl@ss 7.0/7.1:	27180710
Product description (long): Approvals Approvals: Approvals: Approvals: Certificates: Approvals: Approvals: Approvals: Approval overview CSA UR + C-UR VDE	eCl@ss 6.0/6.1:	27180710
Approvals Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC	eCl@ss 5.1/5.1.4:	27180710
Approvals: Approval overview CSA UR + C-UR VDE Certificates: EAC		SK enclosure heater, with fan, 355/400 W, 115 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm
CSA UR + C-UR VDE Certificates: EAC	Approvals	
	Approvals:	CSA UR + C-UR
Declarations: Declaration of conformity	Certificates:	EAC
	Declarations:	Declaration of conformity

© Rittal 2018