

Rittal – The System.

Faster – better – everywhere.

► TopTherm air/air heat exchanger wall-mounted with controller – SK 3128.100

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm air/air heat exchanger wall-mounted with controller – SK 3128.100

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Color: RAL 7035

**Protection category
IP to IEC 60 529:** Internal circuit, IP 54

Supply includes: Complete unit ready for connection
Plug-in terminal strip
Floating fault signal contact in case of overtemperature

Product features

**Specific thermal
output:** 45 W/K

**Air throughput
(unimpeded air flow):** External circuit at 50 Hz: 600 m³/h (353.1 cfm)
External circuit at 60 Hz: 625 m³/h (367.9 cfm)
Internal circuit at 50 Hz: 600 m³/h (353.1 cfm)
Internal circuit at 60 Hz: 625 m³/h (367.9 cfm)

**Rated operating
voltage:** 230 V, 1~, 50 Hz/60 Hz

Dimensions: Height: 950 mm (37 ")
Width: 400 mm (16 ")
Depth: 205 mm (8.1 ")

Temperature control: Electronic Control with Digital Display (factory setting +35°C)

Temperature range: Operation (environment): -5°C...+55°C

Output per fan:	At 50 Hz: 70 W At 60 Hz: 90 W
Rated current (max.):	per fan at 50 Hz: 0.3 A per fan at 60 Hz: 0.4 A
Miniature circuit-breaker/fuse:	2 A
Packaging unit:	1 pc(s).
Weight/packaging unit:	19 kg
EAN:	4028177388970
Customs tariff number:	84158300
ETIM 6.0:	EC002514
ETIM 5.0:	EC002514
eCl@ss 8.0/8.1:	27180711
eCl@ss 7.0/7.1:	27180711
eCl@ss 6.0/6.1:	27180711
eCl@ss 5.1/5.1.4:	27180711
Product description (long):	SK Air/Air heat exchanger TopTherm, wall-mounted with controller, 45 W/K, 230 V, 1~, 50/60 Hz, WHD: 400 x 950 x 205 mm

Approvals

Approvals:	Approval overview UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity