

# Switched Enclosures

## Circuit-Lock® Unfused Disconnect Switches

"Suitable as Motor Disconnect"



UL Listed, CSA Certified  
TYPE 4, 4X and  
12 Enclosure Rating

**IP66**  
SUITABILITY

### 30, 60 and 100 Amp Unfused Disconnect Switches

Description	Catalog Number
30A Circuit-Lock disconnect switch.	<b>HBLDS3</b>
30A Circuit-Lock disconnect switch for use with variable frequency drives.	<b>HBLDS3VFD<sup>A</sup></b>
30A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	<b>HBLDS3AC</b>
30A Circuit-Lock disconnect switch with HBLAC2 aux. contact.	<b>HBLDS3AC2</b>
30A Circuit-Lock disconnect switch without conduit knockout or conduit fitting.	<b>HBLDS3NK</b>
30A Circuit-Lock disconnect switch with HBLAC1 aux. contact without conduit knockout or conduit fitting.	<b>HBLDS3ACNK</b>
30A Circuit-Lock disconnect switch with 3 aux. contacts, w/o conduit knockouts. Break before main break – 1 set "normally open", 1 set "normally closed". Break after main break – 2 sets "normally open", 1 set "normally closed".	<b>HBLDS33ACNK</b>
60A Circuit-Lock disconnect switch.	<b>HBLDS6</b>
60A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	<b>HBLDS6AC</b>
100A Circuit-Lock disconnect switch.	<b>HBLDS10</b>
100A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	<b>HBLDS10AC</b>



**HBLDS3AC**



**HBLAC1**



**HBLAC2**

### Auxiliary Contacts for 30, 60 and 100 Amp Switch, A600 Pilot Duty

Description	Catalog Number
"Break After Main Break", 1 set of n/o contacts, 1 set of n/c contacts.	<b>HBLAC1*</b>
"Break Before Main Break", 1 set of n/o contacts.	<b>HBLAC2*</b>

### Ground Block

Description	Catalog Number
For 30A switches.	<b>HBL30RGB</b>
For 60A and 100A switches.	<b>HBL60100RGB</b>

### Neutral Block

Description	Catalog Number
For 30A switches.	<b>HBL30RNB</b>
For 60A switches.	<b>HBL60RNB</b>
For 100A switches.	<b>HBL100RNB</b>



**HBL30RGB**



**HBL30RNB**

Note: \* Not for use with HBLDS33ACNK.  
30A Units are supplied with one 3/4 in. N.P.T. Raintight conduit fitting.  
60A and 100A Units are supplied with two 1 1/4 in. N.P.T. Raintight conduit fittings.  
<sup>A</sup> See page C-34 for wiring details.