



Representative Image

**Catalog No. TG3221****Description: 30A 2P GD N1 240V FUSIBLE SW****UPC No 783164008494****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG3221

**Descriptors**

Category

General Duty

**Specifications**

Amperage	30 A
Poles	2
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	12-8 AL 14-8 CU
240 Vac, NEC Std, 1-ph	1.5
240 Vac, Time Delay, 1-ph	3
250 Vdc	5
GSA Compliance	Yes

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	10.3
Depth	3.3
Width	6.4
Weight	5

