



Catalog No. TH4366C

Description: 600A 3P HD N1 600V FUSIBLE CSA

UPC No 783164422474

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Suitable for use as service equipment when installed in accordance with the Canadian Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH4366C



Representative Image

Descriptors

| | |
|-------------|------------|
| Category | Heavy Duty |
| GO Schedule | S1 |

Specifications

| | |
|---------------------------|-----------------|
| Voltage | 600 AC |
| Amperage | 600 A |
| Poles | 3 |
| Wires | 4 |
| Fusing | Fusible |
| Enclosure | NEMA 1 (Indoor) |
| Options | CSA SE Rated |
| Wire Range (Cu/Al) | (2) 4-500 |
| 240 Vac, NEC Std, 3-ph | 75 |
| 240 Vac, Time Delay, 3-ph | 200 |
| 480 Vac, NEC Std, 3-ph | 150 |
| 480 Vac, Time Delay, 3-ph | 400 |
| 600 Vac, NEC Std, 3-ph | 200 |
| 600 Vac, Time Delay, 3-ph | 500 |
| 250 Vdc | 50 |
| GSA Compliance | Yes |

Classifications

| | |
|------------|-----|
| cUL Listed | Yes |
| UL Listed | Yes |

Dimensions

| | |
|--------|------|
| Height | 53.9 |
| Depth | 8.3 |
| Width | 22.9 |
| Weight | 132 |

by ABB

