



### Catalog No. THN3361

Description: 30A 3P HD N1 600V NONFUSE SW

UPC No 783164011302

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. THN3361



Representative Image

#### Descriptors

|             |            |
|-------------|------------|
| Category    | Heavy Duty |
| GO Schedule | S1         |

#### Specifications

|                        |                 |
|------------------------|-----------------|
| Voltage                | 600 AC          |
| Amperage               | 30 A            |
| Poles                  | 3               |
| Wires                  | 3               |
| Fusing                 | No Fuse         |
| Enclosure              | NEMA 1 (Indoor) |
| Options                | None            |
| Wire Range (Cu/Al)     | 12-2            |
| 240 Vac, NEC Std, 1-ph | 3.0 hp          |
| 240 Vac, NEC Std, 3-ph | 10.0 hp         |
| 480 Vac, NEC Std, 1-ph | 7.5 hp          |
| 480 Vac, NEC Std, 3-ph | 20.0 hp         |
| 600 Vac, NEC Std, 1-ph | 10.0 hp         |
| 600 Vac, NEC Std, 3-ph | 30.0 hp         |
| 250 Vdc                | 5.0 hp          |
| GSA Compliance         | Yes             |

#### Classifications

|            |     |
|------------|-----|
| cUL Listed | Yes |
| UL Listed  | Yes |

#### Dimensions

|        |         |
|--------|---------|
| Height | 10.3 in |
| Depth  | 4.0 in  |
| Width  | 8.3 in  |
| Weight | 9.0 lb  |

by ABB

